

# 2 Post Lift Comparison Chart

# 2010



	CLFP9	E10	CL10V3	CL10V3-DPC	E12	12000	15000	18000
Capacity	9,000 lbs	10,000 lbs	10,000 lbs	10,000 lbs	12,000 lbs	12,000 lbs	15,000 lbs	18,000 lbs
Lifting Configuration	Symmetric	Versymmetric® 2 Lifts in One	Versymmetric® Plus 2 Lifts in One	Versymmetric® Plus 2 Lifts in One	Symmetric	Symmetric	Symmetric	Symmetric
Arm Configuration	3 stage front + 3 stage rear	3 stage front 2 stage rear	directSPOT™ - offset 3 stage front + 3 stage rear	directSPOT™ - offset 3 stage front + 3 stage rear	2 stage front and rear	2 stage front and rear	2 stage front and rear	2 stage front and rear
Width Overall	11' 5½"	10' 11¾"	Adj. 11' 6½" - 11' 11"	Adj. 11' 6½" - 11' 11"	11' 7¾"	11' 10"	12' 10¾"	12' 10¾"
Drive-thru Clearance	98¾"	98¾"	Adj. 100½" - 105"	Adj. 100½" - 105"	103"	104½"	106¾"	106¾"
Floor-Overhead Switch	N/A	11' 5"	11' 2½"	11' 2½"	13' 3½" or 14½"	13' 1"	13' 11"	13' 11"
Column Height	10" 7/8"	11' 11¾"	11' 8"	11' 8"	13' 10" or 14' 7"	13' 8"	14' 6"	14' 6"
Ceiling Height Required	10' 1¾"	12'	12'	12'	13' 11" or 14' 8"	13' 9"	14' 7"	14' 7"
Adjustable Height Standard	No	No	No	No	Yes	No	No	No
Column Height Extensions	No	Optional	Optional	Optional	Optional	Optional	Optional	Optional
Front Arm Reach	24½" - 44½"	21¾" - 39¼"	19¼" - 42"	19¼" - 42"	35¾" - 54½"	37" - 54"	38½" - 62"	38½" - 62"
Rear Arm Reach	24½" - 44½"	38¼" - 55¾"	37¾" - 60"	37¾" - 60"	35¾" - 54½"	37" - 54"	38½" - 62"	38½" - 62"
Screw Pad Height	3¾" - 7½"	4½" - 7¼"	3¾" - 7½"	3¾" - 7½"	5¼" - 7¼"	5" - 6¾"	6¼" - 8½"	6¼" - 8½"
Stack Adapters	Optional	Optional	Optional	Standard	Standard	Standard	Standard	Standard
Frame Adapters	Optional	Optional	Optional	Optional	Standard	Standard	Standard	Standard
Speed of Rise	60 Sec.	50 Sec.	48 Sec.	48 Sec.	66 Sec.	60 Sec.	80 Sec.	80 Sec.
Motor	2HP	2HP	2HP	2HP	2HP	2HP	2HP	3HP
Voltage	208 - 230v *	208 - 230v *	208 - 230v *	208 - 230v *	208 - 230v *	208 - 230v *	208 - 230v *	208 - 230v *
Electrical Requirements	Dedicated 25 Amp Circuit	Dedicated 25 Amp Circuit	Dedicated 25 Amp Circuit	Dedicated 25 Amp Circuit	Dedicated 25 Amp Circuit	Dedicated 25 Amp Circuit	Dedicated 25 Amp Circuit	Dedicated 25 Amp Circuit
Rubber Door Guards	Standard	Standard	Standard	Standard	Standard	Foam Door Guards	Foam Door Guards	Foam Door Guards
† Custom Paint Colors	No	No	Yes	Yes	No	Yes	Yes	Yes
Lock Release System	Dual-point mechanical lock release	Single-point mechanical lock release	Single-point mechanical lock release	Dual single-point mechanical lock release	Single-point mechanical lock release	Single point air actuated lock release	Single point air actuated lock release	Single point air actuated lock release

† Standard colors are red and blue. Custom colors are available on select lift models with order of 6 or more lifts. \* Single phase standard. Optional 3 phase electrical available. Flooring: Concrete requirements are 4 inches minimum depth, with steel reinforcement, 3500 psi, cured 28 days per commercial practice.