




SX14

SITE SPECIFICATIONS

- **BAY HEIGHT:** 77" rise plus vehicle
- **BAY WIDTH:** 14' recommended
- **BAY DEPTH:** 28' rec. standard
- **POWER REQ.:** 208-230v Single Phase*, 30-amp breaker
- **MIN. CONCRETE SPEC:** 4" thick, reinforced, free from cracks/seams, rated at 3500+ psi, cured at least 28 days

SERVICE BAY LAYOUT



Model Number	SX14	SX14-R
Lifting Capacity	14,000 lbs.	
Rise Height	77"	66.5"
Overall Length	265"	219"
Overall Width	91.25"	
Width of Runways	25.5"	
Between Runways	40"	
Lowered Height	10.5"	-
Maximum Wheelbase	183"	
Wheel Alignment (Max.)	172.75"	
Wheel Alignment (Min.)	70.75"	
Motor	3HP	
Voltage (Single Phase Std.)	208v-240v (23 FLA)	
Speed of rise	75 s	
Air Required	90 - 120 psi (20 CFM)	
Min. Recommended Bay Size	14' x 28'	14' x 24'
ALI/ETL Certified	√	√
Color Available	■	

*3-phase upgrade is available for purchase

Extended Ramps add 18" to SX14