

# 10K INGROUND EV1020

With its small footprint and substantial capabilities, this 10,000 lbs., 3-Stage inground lift is ready for any professional service facility. **Expect a longer life cycle from our chrome guide tubes and non-breathing ram-style cylinders.**

Optional productivity upgrades include our **XP9 Express Service Pad** for quick vehicle spotting and our **QuickCycle™** technology that reduces lift operation time.



MODEL # EV1020

- 12' MINIMUM**
- 12' RECOMMENDED**
- 24' RECOMMENDED**
- 208-230V, 1PH, 30A**
- 90-120 PSI**

MODEL NUMBER	EV1020 / EV1020-QC	EV1020XP9 / EV1020XP9-QC
Description	Standard / <b>QuickCycle™</b>	XP9 / XP9 & <b>QuickCycle™</b>
Lifting Capacity	<b>10,000 lbs.</b>	<b>9,000 lbs.</b>
Arm Configuration	3-Stage Front & Rear	Drive-on Express Pad
Stroke	68"	
Rise Height	74"	70"
<b>Overall Width (A)</b>	97"	79½"
<b>Drive Thru Clearance (B)</b>	7' 3"	NA
<b>Arm Reach (C)</b>	<b>Min. 19⅝" Max. 42⅞"</b>	NA
Platform Length x Width	NA	58"/66½"/75" x 24"
Distance Between Platforms	NA	31½"
Screw Pad Height	3⅞" - 6⅞"	NA
Plunger Diameter	8½"	
Standard Motor/Voltage*	2HP, 208v-230v, 60Hz, 1Ph / <b>3HP, 208v-230v, 60Hz, 1Ph</b>	
Rise Time	38s / <b>24s</b>	38s / <b>24s</b>
<b>Max. Load per Arm</b>	2,500 lbs.	4,500 lbs.
ALI® Certified	<input checked="" type="checkbox"/>	

