

10K VERSYMMETRIC® CL10V3

Equipped with 3-Stage directSPOT™ arms, an industry-first, the CL10V3 will reduce spotting time and boost productivity.

SERVICE BAY SPECIFICATIONS

- HEIGHT:** 12' minimum
- WIDTH:** 14' recommended
- DEPTH:** 24' recommended
- POWER:** 208-230v, 1pH, 30a

CONCRETE
4" thick, reinforced, free from cracks/seams, 3500+ psi & cured 28+ days



PRODUCT SPECIFICATIONS

| MODEL NUMBER | CL10V3 | CL10V3-QC |
|-------------------------------|--|------------------------------|
| Description | Versymmetric® | Versymmetric® w/ QuickCycle™ |
| Lifting Capacity | 10,000 lbs. | |
| Lift Configuration | Versymmetric®, 3-Stage Front & Rear | |
| Rise Height | 74⅞" | |
| Height of Columns | Standard 11' 8" or 11' 2" with 2' or 3' extensions | |
| Max. Extended Cylinder Height | 11' 11" | |
| Adjustable Width Overall (A) | 11' 6½" - 11' 11" | |
| Drive Thru Clearance | 8' 4" / 8' 8½" | |
| Floor to Overhead Switch | Standard 11' 2½" or 10' 8½" with 2' or 3' extensions | |
| Front Arm Reach | Min. 20" Max. 42" | |
| Rear Arm Reach | Min. 37⅝" Max. 60" | |
| Screw Pad Height | Min. 3⅞" Max. 6⅞" | |
| Inside Columns (B) | Min. 9' 2" Max. 9' 6½" | |
| Low Lock Height | 12" Net Rise | |
| Platform Length | NA | |
| Rise Time | 38s | 24s |
| Max. Load per Arm | 2,500 lb. | |
| ALI® Certified | <input checked="" type="checkbox"/> | |

SERVICE BAY LAYOUT

