





# OPEN-TOP 2-POST CLFP9

Challenger's 9,000 lb. capacity 2-post lift boasts standard 3-stage front and rear arms that offer maximum sweep, arm retraction, and reach.

## SERVICE BAY SPECIFICATIONS

-  **HEIGHT:** 10' 2" minimum
-  **WIDTH:** 14' recommended
-  **DEPTH:** 24' recommended
-  **POWER:** 208-230v, 1pH, 20a

**CONCRETE**  
4" thick, reinforced, free from cracks/seams, 3500+ psi & cured 28+ days



## SPECIFICATIONS

MODEL NUMBER	CLFP9
Rise Height	6' 5 <sup>7</sup> / <sub>8</sub> "
Overall Height	10' 7 <sup>8</sup> / <sub>16</sub> "
Overall Width	11' 5 <sup>1</sup> / <sub>2</sub> "
Drive Thru Clearance	8' 2 <sup>3</sup> / <sub>16</sub> "
Front Arm Reach	Min 24 <sup>1</sup> / <sub>2</sub> " Max 44 <sup>1</sup> / <sub>2</sub> "
Rear Arm Reach	Min 24 <sup>1</sup> / <sub>2</sub> " Max 44 <sup>1</sup> / <sub>2</sub> "
Screw Pad Height	Min 4" Max 6"
Rise Time	50s
Required Ceiling Height	10' 1 <sup>1</sup> / <sub>8</sub> "

## SERVICE BAY LAYOUT

