

9K DRIVE-ON PAD LIFT CL10V3-XP9

Low-profile, drive-on style pads provide quick vehicle spotting for express service bays. Ramps flip up and lock to extend the platforms for longer wheelbases.

SERVICE BAY SPECIFICATIONS

- HEIGHT:** 12' minimum
- WIDTH:** 14' recommended
- DEPTH:** 24' recommended
- POWER:** 208-230v, 1pH, 30a

CONCRETE
4" thick, reinforced, free from cracks/seams, 3500+ psi & cured 28+ days



PRODUCT SPECIFICATIONS

MODEL NUMBER	CL10-XP9	CL10-XP9-DPC-QC
Description	Drive-on Pad Lift	Drive-on Pad Lift, DPC & QuickCycle™
Lifting Capacity	9,000 lbs.	
Rise Height (A)	70"	
Height of Columns	Standard 11' 8" or 11' 2" w/ 2' or 3' extensions	
Max. Extended Cylinder Height	11' 11"	
Adjustable Width Overall	11' 6½" - 11' 11"	
Drive Thru Clearance	90"	
Floor to Overhead Switch	Standard 11' 2½" or 10' 8½" w/ 2' or 3' extensions	
Low Lock Height	12" Net Rise	
Platform Length	58" / 66½" / 75"	
Standard Motor/Voltage	2HP, 208v-230v, 60Hz, 1Ph	3HP, 208v-230v, 60Hz, 1Ph
Rise Time	38s	24s
Max. Load per Arm	NA	
Required Ceiling Height	12' Minimum	
ALI® Certified	<input checked="" type="checkbox"/>	

SERVICE BAY LAYOUT

